





Meet the world's no. 1 in collaborative robots

Universal Robots is not just a name. When we say universal we mean it. The UR arms can be implemented in virtually any industry, in any process and by any employee. Around the world, more than 10,000* operating UR robots are testimony to just that – and to the clear objective we've had from the very beginning: To make collaborative robot technology accessible to companies of all sizes.

Robots are our life. So whether you are looking for a robotic solution for the sake of precision, speed, optimization or ergonomics, we can help you. And probably at a price that will take you by surprise; our robotic arms have an average payback time of just 195 days, which makes them the most favorable on the market, within reach of most companies. But that is far from the only reason why Universal Robots is the world's no. 1 in collaborative robots:

With our TÜV-certified robots by your side, you are in the safest of hands. The UR robots can work collaboratively right alongside employees due to built-in force-sensing causing the robots to automatically stop operating when they encounter obstacles in their route. The robot can be programmed to operate in reduced mode when a person enters the work zone. When we say collaborative we don't, however, just apply the term to safety. We use it in a much wider sense; while safety is imperative, we believe that being collaborative is as much about being user-friendly, easily re-deployable and accessible. In our opinion the future is collaborative – and we are here to bring it to you

"The UR5 does in 4 hours what it would take manual labor 2-3 days to accomplish. This progress has made it possible for us to compete with overseas manufacturers and bring back manufacturing jobs to the US."

Geoff Escalette CEO, RSS Manufacturing

Five fast benefits for your business

FAST SET-UP

the first time they are to set up a UR robot arm. Unpacking the robot, mounting it and programming the first simple task typically takes less than an hour. As experienced by our customers, the average time to carry out a complete set-up is just half a day.

FLEXIBLE DEPLOYMENT

Production set-ups today often need to be flexible and agile in order to meet changing demands and stay competitive. And Universal Robots won't be the one to limit you; on the contrary, our light-weight UR robot arms are easily moved and re-deployed to new processes, enabling you to automate virtually any manual task, including those with small batches or fast change-overs.

EASY PROGRAMMING

The days of hiring expensive external consulting every time a robot has to be programmed are over.


The new reality is this: Operators with no programming experience can quickly program the UR robot arms thanks to patented, intuitive 3D visualization. All he or she needs to do is move the robot arm to the desired waypoints or touch the arrow keys on the easy-to-use touchscreen tablet.

FASTEST PAYBACK IN THE INDUSTRY

If you have always considered automation out of reach, it's time to reconsider. The collaborative UR robot arms come with an average payback time of 195 days. That's the fastest in the industry — quite simply because UR robot arms are void of all the added costs traditionally associated with automation such as external programming resources and shielded work cells.

COLLABORATIVE AND SAFE


Universal Robots has been the frontrunner of collaborative robotics since the term was coined so rest assured that you are in the safest of hands when you choose our robots. More than 80% of the UR robot arms in operation worldwide works right next to humans – with no safety guards to shield them. And cobots are more than happy to do the jobs that human operators find repetitive and dull.



Meet the market's most collaborative family

Take flexibility, then add intelligence, endurance and outstanding precision and you have a UR robot arm.

The UR family has three members: The UR3, the UR5 and the UR10 – each named after their payload capacity in kilograms and each with outstanding collaborative abilities that will make them a favorite on the production line.





EN ISO 13849-1 PL 'd'







The smallest member of the UR family, the UR3 table-top robot is the perfect choice for light assembly tasks and jobs that call for absolute precision. With 360-degree rotation on all wrist joints and infinite rotation on the end joint, the UR3 is the most flexible, versatile and collaborative robot on the market today.

UR3 IN SHORT

- Automates tasks up to 3 kg (6.6 lbs)
- Reach radius of up to 500 mm (19.7 in)

THE UR5

The slightly bigger UR5 is ideal for automating low-weight processing tasks like picking, placing and testing.

The medium-sized robot arm is easy to program, fast to set up and, just like the other collaborative members of the UR family, offers one of the fastest payback times in the industry.

UR5 IN SHORT

- Automates tasks up to 5 kg (11 lbs)
- Reach radius of up to 850 mm (33.5 in)

THE UR10

While the largest robot arm in the UR family and the one with the most muscle power, the UR10 does not compromise on precision. The collaborative robot arm will automate heavier-weight process tasks with payload requirements of up to 10 kg.

UR10 IN SHORT

- Automates tasks up to 10 kg (22 lbs)
- · Reach radius of up to 1300 mm (51.2 in)

Thanks to the reach radius of 1300 mm the UR10 robot arm is especially suitable for e.g. packaging, palletizing, assembly and pick and place where the distance between the different operating areas is longer.

Automate virtually

anything

When we say the UR robot arms can automate virtually anything we mean virtually anything; from assembly to painting, from screw driving to labeling, from packing to polishing, from injection molding to welding and whatever other processing task you can think of. And thanks to the flexibility of the UR family, the robot arms are even economically viable for small-batch and mixed-product assembly.



SCREW DRIVING

POLISHING

Let a UR robot arm repeat the

same movement over and over with

exactly the same precision and speed to improve

the quality and consistency of your products.



PACKAGING AND PALLETIZING

Make sure that your deliveries are always correctly counted and packaged to the strictest standards by letting the UR robot arm do the job for you.



INJECTION MOLDING

The UR robot arm can be used across all areas of plastic and polymer production and can tend presses with never-failing accuracy and consistency.



(=

The UR robot arm sands and polishes even curved and uneven surfaces with adjustable force for a consistent result.



LAB ANALYSIS

Relieve workers from repetitive work with a UR robot arm to increase objectiveness in your analysis and testing processes.



GLUING, DISPENSING AND WELDING

The UR robot arm can add efficiency to your gluing, dispensing and welding processes, e.g. by constantly dosing and injecting exactly the same quantity of material or by always performing each weld to the highest accuracy.



MACHINE TENDING

The UR robot arm can be used to run most machine tending applications autonomously and is quickly adaptable to new products on the production line.



ASSEMBLY

The UR robot arm effortlessly handles assembly of plastics, woods, metals and a range of other materials while improving speed and quality in the process.




PICK AND PLACE

A UR robot arm can run most pick and place tasks autonomously and in doing so is able to reduce cycle times and material waste.



QUALITY INSPECTION

A UR robot arm with an inspection camera will identify and pinpoint defective or faulty parts before they are packaged or shipped to maintain high product quality.




Programming a UR robot arm is pure child's play

When you choose Universal Robots, intuitive programming is all part of the deal. One of the most tangible benefits is that you can easily re-program the UR robot arms yourself and make use of automation wherever and whenever it best suits you.

The UR robots are designed to mimic the range of motion of a human arm and incidentally all it takes to program and reprogram the robotic arms is a human arm. It doesn't get any easier – and perhaps most importantly it eliminates the need for expensive third-party programmers every time you want to assign the robot arm to a different task.

The intuitive software allows even the most inexperienced user to quickly grasp the basics of programming and set waypoints by simply moving the robot into position. And if you have recurring tasks, programs can be stored in the UR robot arm and re-used. It's pure child's play.



ONLINE TRAINING AT YOUR CONVENIENCE

Universal Robots Academy is our new online training program. Through engaging hands-on experiences, simulations and interactive robot animations you will quickly acquire the skills to program and operate a UR robot without any further assistance.

Access the Universal Robots Academy whenever and wherever you want to — it is open 24/7 and completely free of charge. Begin your online training on universal-robots.com/academy







we thought could do the job. It's got the speed and precision of a standard industrial robot with the ability to move around and work next to humans."

A mobile fleet of UR robots is now deployed flexibly throughout the sheet metal department, integrating them in the entire production cycle from cutting the initial blank on the blanking press to forming, folding and final assembly of the electrical components.

Read the case in full at: universal-robots.com/case-stories

Technical details

	UR3		UR5		UR10	UR10	
Performance							
Repeatability	±0.1 mm / ±0.0039 ii	n (4 mils)	±0.1 mm / ±0.0039 i	in (4 mils)	±0.1 mm / ±0.0039 in	ı (4 mils)	
Ambient temperature range	0-50° *		0-50°				
Power consumption	Min 90W, Typical 12	5W, Max 250W	Min 90W, Typical 15	0W, Max 325W	Min 90W, Typical 250	W, Max 500W	
Collaboration operation	15 advanced adjustable safety functions. TüV NORD Approved Safety Function Tested in accordance with: EN ISO 13849:2008 PL d		15 advanced adjustable safety functions. TüV NORD Approved Safety Function Tested in accordance with: EN ISO 13849:2008 PL d		TüV NORD Approved Tested in accordance	15 advanced adjustable safety functions. TüV NORD Approved Safety Function Tested in accordance with: EN ISO 13849:2008 PL d	
Specification							
Payload	3 kg / 6.6 lbs		5 kg / 11 lbs		10 kg /22 lbs		
Reach	500 mm / 19.7 in		850 mm / 33.5 in		1300 mm / 51.2 in		
Degrees of freedom	6 rotating joints		6 rotating joints		6 rotating joints	<u> </u>	
Programming	Polyscope graphical user interface on 12 inch touchscreen with mounting		Polyscope graphical user interface on 12 inch touchscreen with mounting			Polyscope graphical user interface on 12 inch touchscreen with mounting	
Movement							
Axis movement robot arm	Working range	Maximum speed	Working range	Maximum speed	Working range	Maximum speed	
Base	± 360°	± 180°/Sec.	± 360°	± 180°/Sec.	± 360°	± 120°/Sec.	
Shoulder	± 360°	± 180°/Sec.	± 360°	± 180°/Sec.	± 360°	± 120°/Sec.	
Elbow	± 360°	± 180°/Sec.	± 360°	± 180°/Sec.	± 360°	± 180°/Sec.	
Wrist 1	± 360°	± 360°/Sec.	± 360°	± 180°/Sec.	± 360°	± 180°/Sec.	
Wrist 2	± 360°	± 360°/Sec.	± 360°	± 180°/Sec.	± 360°	± 180°/Sec.	
Wrist 3	Infinite	± 360°/Sec.	± 360°	± 180°/Sec.	± 360°	± 180°/Sec.	
Typical tool		1 m/Sec. / 39.4 in/Sec.		1 m/Sec. / 39.4 in/Sec.		1 m/Sec. / 39.4 in/Sec.	
Features							
IP classification	IP64		IP54		IP54		
ISO Class Cleanroom	5		5		5		
Noise	70dB(A)		72dB(A)		72dB(A)		
Robot mounting	Any		Any		Any		
I/O ports	Digital in	2	Digital in	2	Digital in	2	
·	Digital out	2	Digital out	2	Digital out	2	
	Analog in	2	Analog in	2	Analog in	2	
I/O power supply in tool	Analog out 12 V/24 V 600 mA in	0 n tool	Analog out 12 V/24 V 600 mA ir	n tool	Analog out 12 V/24 V 600 mA in	tool	
Physical							
Footprint	Ø 128mm		Ø 149mm		Ø 190mm		
Materials	Aluminium, PP plastics		Aluminium, PP plastics		Aluminium, PP plastics		
Tool connector type	M8		M8			M8	
Cable length robot arm	6 m / 236 in		6 m / 236 in		6 m / 236 in		
Weight with cable	11 kg /24.3 lbs		18,4 kg / 40.6 lbs		28,9 kg / 63.7 lbs		

CONTROL BOX

- 6	-0	21	tu	r	0

IP classification	IP20		
ISO Class Cleanroom	6		
I/O ports	Digital in	16	
	Digital out	16	
	Analog in	2	
	Analog out	2	
I/O power supply	24V 2A		
Communication	TCP/IP 100Mbit, M	odbus TCP, Profinet, EthernetIP	
Power source	100-240 VAC, 50-60 Hz		
Ambient temperature range	0-50°		

Physic

Control box size (WxHxD)	475 mm x 423 mm x 268 mm / 18.7 x 16.7 x 10.6 ii			
Weight	UR3, UR5	15 kg / 33.1 lbs		
	UR10	17 kg / 37.5 lbs		
Materials	Steel			

TEACH PENDANT

Feature

IP classification

Physical	
Materials	Aluminium, PP
Weight	1,5 kg / 3.3 lbs
Cable length	4,5 m / 177 in





^{*} The robot can work in a temperature range of 0-50°C. At high continuous joint speed, ambient temperature is reduced.

Contact your local distributor

All UR robot arms are sold worldwide through authorized distribution partners who have the knowhow to customize the automation solution that perfectly suits the requirements in your production.

Find the distribution partner closest to you at universal-robots.com/distributors. Simply locate your continent and you will get a list of distributors in your corner of the world.



E. MISSOURI & ILLINOIS 2021 Congressional Dr. St. Louis, MO 63146

W. MISSOURI & KANSAS 8004 Reeder St. Lenexa, KS 66214

Great Lakes Office:

Universal Robots USA, Inc.

5430 Data Court, Suite 300 Ann Arbor, Michigan 48108

United States

Phone: +1 734 249 6016

East Coast Office:

Universal Robots USA, Inc.

100 Quentin Roosevelt Blvd, Suite 206

Garden City, New York 11530

United States

Phone: +1 844-462-6268

West Coast Office:

Universal Robots USA, Inc.

101 Pacifica, Suite 350 Irvine, California 92618

United States

Phone: +1 949 236 6082

South Central US - LATAM Office:

Universal Robots USA, Inc.

Tower 909 Building, 909 Lake Carolyn Parkway, Suite 1850

Irving, Texas 75039

United States

Phone: +1 469 284 8520

www.universal-robots.com sales@universal-robots.com

